



WATER HEATERS FOR VERTICAL MOUNTING ON THE WALL										
CHARACTERISTICS										
Model	...	72269(H)	72267(H)	72268(H)	72265(H)	72270(H)	72266(H)	72280M(H)	72280(H)	72281(H)
Rated volume	L	30	50	80	80	100	120	150	150	200
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Rated voltage	V	220-230~	220-230~	220-230~	220-230~	220-230~	220-230~	220-230~	220-230~	220-230~
Rated electrical power	kW	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	2,0; 3,0	2,0; 3,0	2,0; 3,0
Maximum D.H.W. tank temperature in	°C	75	75	75	75	75	75	75	75	75
Weight when empty	kg	15 (14(H))	19 (16.5(H))	27 (22(H))	27 (22(H))	30 (26(H))	35 (30(H))	43.5 (37(H))	48 (42(H))	60 (53.5(H))
CONNECTIONS										
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		-	-	-	-	-	-	-	-	-
4: Control panel		-	-	-	-	-	-	-	-	-
5: Flange with heating element		-	-	-	-	-	-	-	-	-
DIMENSIONS										
A	mm	555	750	1065	825	1000	1165	1415	1015	1255
B	mm	470	665	980	740	915	1080	1330	930	1170
C	mm	145	145	145	175	175	175	175	190	190
D	mm	385	385	385	460	460	460	460	586	586
E	mm	80	80	80	96	96	96	96	105	105
F	mm	400	400	400	474	474	474	474	600	600
G	mm	32	32	32	32	32	32	32	43	43
M	mm	-	-	-	-	-	-	1003	560	780

Symbol:  
H - stainless steel tank